



Technical Data Sheet (TDS)

Issued by:

NYS Inc.

4-3-12-508 Tsukiji, Chuo-ku, Tokyo 104-0045, Japan

TEL: +81-70-9002-4439

Email: info@nys-chemicals.jp

OEM FILM INSTALLATION SOLUTION – CONCENTRATED TYPE

Product Lineup

- OEM Film Installation Solution - Concentrated Type 400ml

1. Product Concept

This product is a highly concentrated installation solution developed specifically for installing paint protection films (PPF) and window films.

With just one push (approx. 1.5 ml) diluted in about 2 L of water, it provides exceptional cost efficiency.

The formulation excludes ingredients that may affect the adhesive layer of the film, significantly reducing the risk of peeling or adhesive degradation not only immediately after installation but also in long-term use.

It is a professional-grade solution designed with safety and film compatibility as top priorities.



2. Composition & Key Features

- Type: Highly concentrated installation solution for PPF and window films
- Form: Liquid
- Recommended Usage Amount: Approx. 1.5 ml per vehicle
- Applicable Materials: All PPF and window films
- Finish: Optimizes film adhesion and slip performance

Key Features

- Ultra-concentrated formula; dilute 1.5 ml with 2 L of water
- Safe formulation that does not harm film adhesive layers
- Reduces long-term risks such as peeling and adhesive deterioration
- Highly compatible with a wide range of film products

3. Performance & Characteristics

This installation solution is engineered to facilitate smooth and efficient installation of PPF and window films, providing a well-balanced combination of slip and initial adhesion.

It eliminates chemical components commonly found in general detergents that can degrade adhesive layers, and the formula has been refined through repeated compatibility testing with multiple films.

As a highly concentrated solution, it offers long-term stability and meets the quality demands of professional installers.

4. Recommended Application Areas

- Paint protection film (PPF) installation
- Window film installation
- Support for car wrapping film installation
- Slip and alignment assistance during installation of various protection films



5. Application Method

1. Add one push (approx. 1.5 ml) of the product into about 2 L of water.
2. Shake well to create a uniform installation solution.
3. After installation, thoroughly rinse off any remaining solution from the film edges before pressing the film down.

6. Precautions During Application

- Do not use undiluted. Always dilute according to the recommended ratio.
- Failure to properly rinse off residual installation solution from film edges may cause adhesion issues.
- Do not mix with other detergents or chemicals.
- Avoid installation under direct sunlight or in high-temperature environments.

7. Summary of Product Properties

- Type: Highly concentrated installation solution for PPF and window films
- Usage per Vehicle: Approx. 1.5 ml
- Core Functions: Assists with film slip and positioning; protects adhesive layers
- Application Method: Dilution with water and spray application
- Material Safety: Designed to avoid negative effects on film adhesive layers
- Applicable Work: All PPF and window film installation
- Application Difficulty: Beginner to intermediate
- Country of Origin: Japan

8. Remarks

- Incorrect dilution may affect workability and adhesion. Follow the recommended ratio.
- Slip characteristics may vary depending on the film type. Adjust dilution as needed.
- Keep out of reach of children.



- Store in a cool, dry place away from direct sunlight.

Issued by:

NYS Inc.

4-3-12-508 Tsukiji, Chuo-ku, Tokyo 104-0045, Japan

TEL: +81-70-9002-4439

Email: info@nys-chemicals.jp

The information contained in this Technical Data Sheet is based on current technical knowledge at the time of publication.

Specifications and details are subject to change without prior notice.