



Technical Data Sheet (TDS)

Issued by:

NYS Inc.

4-3-12-508 Tsukiji, Chuo-ku, Tokyo 104-0045, Japan

TEL: +81-70-9002-4439

Email: info@nys-chemicals.jp

OEM PAINT GLASS COATING – 3-MONTH DURABILITY TYPE

Product Lineup

- OEM Paint Glass Coating 3-Month Durability Type 50ml
- OEM Paint Glass Coating 3-Month Durability Type 800ml
- OEM Paint Glass Coating 3-Month Durability Type 4L
- OEM Paint Glass Coating 3-Month Durability Type 18L
- OEM Paint Glass Coating 3-Month Durability Type 20L

1. Product Concept

This product is a glass coating that provides hydrophobicity, gloss, and anti-stain protection through simple spray application after washing.

It ensures consistent, high-quality results for both professionals and general users.

A single application protects the surface for approximately 1–3 months, reducing maintenance frequency while maintaining gloss.



2. Composition & Key Features

- Type: Glass coating (spray type)
- Form: Liquid
- Recommended Usage Amount: Approx. 20 ml per vehicle
- Applicable Materials: Painted surfaces, unpainted plastics, rubber, glass, and motorcycle/bicycle frames
- Finish: High-gloss, water-repellent type

Key Features

- Easy and uniform application
- Excellent water repellency and anti-stain performance
- Protects against UV rays, acid rain, bird droppings, and tree sap
- Short application time with professional-grade results

3. Performance & Characteristics

Hydrophobic & Anti-Stain Performance

Creates a durable water-repellent layer that minimizes adhesion of water, dirt, and oil. Maintains a clean, glossy surface with a water contact angle exceeding 100°.

Gloss Enhancement

Provides deep gloss and clarity while preventing oxidation and oily film buildup.

Environmental Resistance

Protects the paint surface from UV rays, acid rain, and organic contaminants.

Ease of Application

Simply spray and spread evenly for a quick, streak-free finish.

4. Recommended Application Areas



- Painted vehicle body panels (hood, doors, fenders, bumpers, etc.)
- Unpainted plastic parts
- Rubber trim components
- Glass surfaces (windshield, windows, mirrors)
- Motorcycle and bicycle painted surfaces

5. Application Method

1. Rinse off dust and dirt thoroughly.
2. Wash with a neutral shampoo and rinse completely.
3. While the surface remains wet, spray evenly.
4. Spread using a sponge or soft microfiber cloth.
5. Lightly rinse before drying.
6. Wipe off remaining water with a microfiber towel.

6. Precautions During Application

- Avoid working under direct sunlight or on hot surfaces.
- Do not over-apply to prevent uneven results.
- Rinse the nozzle lightly with water after use and close tightly.

7. Summary of Product Properties

- Type: Glass coating (spray type)
- Form: Liquid
- Usage per Vehicle: Approx. 20 ml
- Durability: Approx. 1-3 months
- Water Contact Angle: Over 100°
- Gloss Level: High
- Anti-Stain Performance: High
- Application Difficulty: Very easy (for beginners)



- Country of Origin: Japan

8. Remarks

- Suitable for both professional and consumer use.
- Durability may vary depending on environmental and surface conditions.
- This document provides technical reference information and does not guarantee performance.

Issued by:

NYS Inc.

4-3-12-508 Tsukiji, Chuo-ku, Tokyo 104-0045, Japan

TEL: +81-70-9002-4439

Email: info@nys-chemicals.jp

The information contained in this Technical Data Sheet is based on current technical knowledge at the time of publication.

Specifications and details are subject to change without prior notice.