



Technical Data Sheet (TDS)

Issued by:

NYS Inc.

4-3-12-508 Tsukiji, Chuo-ku, Tokyo 104-0045, Japan

TEL: +81-70-9002-4439

Email: info@nys-chemicals.jp

OEM PAINT MAINTENANCE AGENT

Product Lineup

- OEM Paint Maintenance Agent 50ml
- OEM Paint Maintenance Agent 80ml
- OEM Paint Maintenance Agent 500ml
- OEM Paint Maintenance Agent 4L
- OEM Paint Maintenance Agent 18L
- OEM Paint Maintenance Agent 20L

1. Product Concept

A maintenance liquid designed for durable coatings (curing-type ceramic/glass) and spray-type quick coatings.

It removes water spots and light staining, reduces the visibility of micro-scratches, and restores hydrophobicity and gloss, helping keep the coated finish cleaner with less effort.

This product is intended to improve maintenance efficiency while minimizing stress on existing coating films.



2. Composition & Key Features

- Type: Wipe-off maintenance liquid for coated paint
- Compatibility: Curing-type ceramic/glass coatings and spray-type coatings
- Recommended Usage Amount: Approx. 15 ml per vehicle
- Application Method: Apply and wipe off immediately (hand application with sponge / polisher-capable)
- Finish: Restored water repellency and gloss; improved clarity

Key Features

- Removes water spots and light contamination; helps suppress re-adhesion
- Restores water repellency and sheeting behavior to improve anti-stain performance
- Makes fine micro-scratches less visible (filling/leveling effect)
- Gentle formulation designed with typical coating films in mind

3. Performance & Characteristics

Cleaning Performance

Effectively removes water spots, traffic film, and light acid-rain marks that dull coated surfaces.

Restoration of Water Repellency & Anti-Soiling Performance

Refines the surface to restore hydrophobicity and sheeting behavior, reducing contaminant adhesion.

Gloss

Enhances surface smoothness to recover gloss and visual clarity.

Workability

Simple apply-and-wipe process; consistent results by hand or with a polisher.

Compatibility

Designed for use on common curing-type and spray-type coatings. Universal compatibility cannot be guaranteed.



4. Recommended Application Areas

- Painted body panels (hood, roof, doors, fenders, bumpers, etc.)
- Painted mirror housings and pillar trims
- Motorcycle painted parts

5. Application Method

1. Pressure-rinse to remove dust and mud, then wash thoroughly with a neutral car shampoo.
2. Dry the surface to remove all remaining moisture.
3. Apply a small amount of product and polish with a sponge or a polisher.
4. When gloss appears, wipe off with a clean microfiber towel to finish.

(For polisher use, work at low speed and light pressure.)

6. Precautions During Application

- Avoid direct sunlight and hot panels.
- Work panel by panel; do not cover overly large areas at once.
- Do not allow the product to dry—wipe off promptly after application.
- For matte or special finishes, repainted areas, and PPF or wraps, perform a spot test in an inconspicuous area before full application.

7. Summary of Product Properties

- Type: Wipe-off maintenance liquid for coated paint
- Compatibility: Curing-type ceramic/glass and spray-type coatings
- Usage per Vehicle: Approx. 15 ml
- Core Functions: Removes water spots and light stains; restores water repellency and gloss;



visually reduces fine micro-scratches

- Application Method: Hand application (sponge) or polisher (low speed, light pressure)
- Country of Origin: Japan

8. Remarks

- Guidance is based on formulation intent and field usage; compatibility with all coatings cannot be guaranteed.
- Always perform a spot test in an inconspicuous area prior to full application.
- This document provides technical reference information and does not guarantee performance.

Issued by:

NYS Inc.

4-3-12-508 Tsukiji, Chuo-ku, Tokyo 104-0045, Japan

TEL: +81-70-9002-4439

Email: info@nys-chemicals.jp

The information contained in this Technical Data Sheet is based on current technical knowledge at the time of publication.

Specifications and details are subject to change without prior notice.