



Technical Data Sheet (TDS)

Issued by:

NYS Inc.

4-3-12-508 Tsukiji, Chuo-ku, Tokyo 104-0045, Japan

TEL: +81-70-9002-4439

Email: info@nys-chemicals.jp

OEM WATERLESS PAINT COATING SPRAY TYPE

Product Lineup

- OEM Waterless Paint Coating - Spray Type 50ml
- OEM Waterless Paint Coating - Spray Type 800ml
- OEM Waterless Paint Coating - Spray Type 4L
- OEM Waterless Paint Coating - Spray Type 18L
- OEM Waterless Paint Coating - Spray Type 20L

1. Product Concept

A completely waterless spray-type coating developed to clean and protect painted surfaces without the need for washing facilities.

Designed for mobility, eco-friendliness, and convenience, it can be used in locations where water is not available, such as apartments, outdoor areas, mobile detailing, or event sites.

Simply spray and wipe to achieve hydrophobicity, anti-stain protection, and gloss enhancement lasting approximately 1–3 months.



2. Composition & Key Features

- Type: Waterless spray-type coating
- Form: Liquid
- Recommended Usage Amount: Approx. 30 ml per vehicle
- Applicable Materials: Painted panels, unpainted plastic, rubber, glass
- Finish: High gloss, hydrophobic, anti-stain

Key Features

- Usable anywhere – no water or washing equipment required
- Quick spray-and-wipe application with hydrophobic and anti-stain performance
- Designed to withstand hot and dry climates

3. Performance & Characteristics

Water Repellency

Forms a polymer-based hydrophobic film that repels water and reduces surface wetting.

Restoration of Water Repellency & Anti-Soiling Performance

Maintains surface cleanliness by reducing adhesion of dirt, oils, and contaminants.

Gloss

Enhances color depth and clarity through a transparent protective layer.

Workability

Simple spray-and-wipe operation with no rinsing required.

Compatibility

Suitable for painted surfaces, unpainted plastics, rubber, and glass.

Cleaning Performance

Safely removes light dust and surface film without the use of water.



Safety

Designed for routine use with minimal impact on existing coatings.

4. Recommended Application Areas

- Painted body panels (hood, roof, doors, fenders, bumpers, etc.)
- Unpainted plastic components and rubber parts
- Glass surfaces
- Motorcycle and bicycle painted sections
- Large vehicles such as RVs, trucks, and campers

5. Application Method

1. Remove dust or loose debris from the surface.
2. Spray the product onto the surface or onto a clean microfiber cloth.
3. Wipe evenly with a damp, well-wrung microfiber towel.
4. Check the surface for uniform gloss to complete the application.

6. Precautions During Application

- Avoid using the product on hot surfaces or under direct sunlight.
- Dust or sand remaining on the surface may cause scratches.
- Always use clean microfiber towels and change surfaces frequently.

7. Summary of Product Properties

- Product Type: Waterless spray-type coating
- Usage per Vehicle: Approx. 30 ml
- Durability: Approx. 1-3 months



- Core Functions: Light cleaning, gloss enhancement, hydrophobic and anti-stain protection
- Application Method: Spray → wipe (Wipe-On / Wipe-Off)
- Suitable Environments: Locations without water access, outdoor areas, hot and dry regions
- Country of Origin: Japan

8. Remarks

- This product is designed for simplified application and differs from curing-type coatings.
- Actual performance and durability depend on surface condition and environment.
- This document provides technical reference information and does not guarantee product performance.

Issued by:

NYS Inc.

4-3-12-508 Tsukiji, Chuo-ku, Tokyo 104-0045, Japan

TEL: +81-70-9002-4439

Email: info@nys-chemicals.jp

The information contained in this Technical Data Sheet is based on current technical knowledge at the time of publication.

Specifications and details are subject to change without prior notice.