



Technical Data Sheet (TDS)

Issued by:

NYS Inc.

4-3-12-508 Tsukiji, Chuo-ku, Tokyo 104-0045, Japan

TEL: +81-70-9002-4439

Email: info@nys-chemicals.jp

OEM PAINT COATING WATER-REPELLENT GLOSS ENHANCER

Product Lineup

- OEM Paint Coating Water-Repellent Gloss Enhancer 50ml
- OEM Paint Coating Water-Repellent Gloss Enhancer 800ml
- OEM Paint Coating Water-Repellent Gloss Enhancer 4L
- OEM Paint Coating Water-Repellent Gloss Enhancer 18L
- OEM Paint Coating Water-Repellent Gloss Enhancer 20L

1. Product Concept

A spray-type coating that provides water repellency and a natural gloss finish with effortless spray-and-wipe application.

It enhances appearance after washing and helps maintain the vehicle's clean condition.

Balanced for hydrophobic, glossy, and anti-stain effects, it is suitable for regular care and finish maintenance.



2. Composition & Key Features

- Type: Spray-type water-repellent gloss enhancer
- Form: Liquid spray
- Recommended Usage Amount: Approx. 20 ml per vehicle
- Applicable Materials: Painted body panels, unpainted plastic trims, rubber trims, motorcycle and bicycle painted surfaces
- Finish: Natural gloss with water repellency

Key Features

- Quick and easy application for all users
- Provides balanced water repellency and light gloss enhancement
- Helps protect paint from contaminants and UV exposure
- Ensures even, streak-free finish with minimal effort
- Ideal for post-wash finishing or routine maintenance

3. Performance & Characteristics

Water Repellency

Forms a uniform hydrophobic layer that helps water slide off easily and reduces spotting or dirt adhesion.

Restoration of Water Repellency & Anti-Soiling Performance

Maintains surface cleanliness by reducing adhesion of light contaminants.

Gloss

Adds a natural, clean-looking shine, subtly enhancing paint color and clarity.

Workability

Simple spray-and-wipe process with low risk of streaking.

Compatibility



Suitable for painted surfaces, unpainted plastics, rubber trims, and motorcycle/bicycle painted areas.

Cleaning Performance

Supports light surface cleaning during post-wash finishing.

Safety

Designed for routine use and compatible with existing coatings.

4. Recommended Application Areas

- Painted body panels (hood, roof, doors, bumpers, etc.)
- Unpainted plastic and rubber trims
- Motorcycle and bicycle painted surfaces

5. Application Method

1. Rinse off dust and dirt thoroughly.
2. Wash with a neutral shampoo and rinse completely.
3. While the surface remains wet, spray evenly.
4. Spread using a sponge or soft microfiber cloth.
5. Lightly rinse before drying.
6. Wipe off remaining water with a microfiber towel.

6. Precautions During Application

- Avoid use under direct sunlight or on hot panels.
- Do not over-apply – use moderate amount to prevent streaks.
- Rinse or clean the spray nozzle after use and store tightly sealed.



7. Summary of Product Properties

- Product Type: Spray-type water-repellent gloss enhancer
- Form: Liquid spray
- Usage per Vehicle: Approx. 20 ml
- Durability: Approx. 1 month
- Gloss Level: Moderate (natural shine)
- Water Repellency: Medium to high
- Anti-Stain Performance: Moderate
- Application Difficulty: Very easy (beginner-friendly)
- Country of Origin: Japan

8. Remarks

- Designed for finishing and routine maintenance after washing.
- Compatible as a top-up product over existing coatings.
- Reapply when water repellency or gloss declines.
- Regular use helps maintain surface cleanliness and appearance.
- Avoid using strong acidic or alkaline cleaners.
- This document provides technical reference information and does not guarantee performance.

Issued by:

NYS Inc.

4-3-12-508 Tsukiji, Chuo-ku, Tokyo 104-0045, Japan

TEL: +81-70-9002-4439

Email: info@nys-chemicals.jp

The information contained in this Technical Data Sheet is based on current technical knowledge at the time of publication.

Specifications and details are subject to change without prior notice.