



Technical Data Sheet (TDS)

Issued by:

NYS Inc.

4-3-12-508 Tsukiji, Chuo-ku, Tokyo 104-0045, Japan

TEL: +81-70-9002-4439

Email: info@nys-chemicals.jp

OEM HIGH PURITY CARNAUBA WAX

Product Lineup

- OEM High Purity Carnauba Wax 225kg (15kg × 15)

1. Product Concept

This product is a professional-grade wax formulated with high-purity carnauba as its primary component.

It is designed to provide deep gloss, natural shine, and reliable surface protection through hand application.

Developed for OEM bulk supply, it emphasizes stable quality and consistent finishing performance for professional use.

2. Composition & Key Features

- Type: Solid wax (carnauba-based)
- Form: Solid block



- Recommended Usage Amount: Approx. 30 g per vehicle
- Applicable Materials: Automotive painted surfaces (clear coat)
- Finish: Deep gloss, natural shine, smooth protective film

Key Features

- Rich, deep gloss derived from high-purity carnauba
- Forms a uniform and smooth protective wax layer
- Optimized for hand application and manual finishing
- Bulk specification suitable for OEM and professional operations

3. Performance & Characteristics

Gloss Characteristics

High-purity carnauba enhances depth and warmth, delivering a natural, premium gloss unique to wax finishes.

Film Formation

Creates a smooth wax film on the paint surface, helping reduce light contamination and moisture adhesion.

Surface Feel & Appearance

Improves surface smoothness and delivers a refined tactile finish after application.

4. Recommended Application Areas

- Automotive painted surfaces
(body panels, doors, hood, trunk, etc.)

5. Application Method

1. Thoroughly wash and dry the vehicle, removing all contamination and grease.



2. Take an appropriate amount of wax on an applicator or cloth and spread thinly and evenly.
3. Allow a few minutes for hazing, then buff with a soft cloth.
4. Check the surface and rebuff any remaining residue.

6. Precautions During Application

- Avoid use under direct sunlight or on hot surfaces.
- Excessive application may result in uneven finishing or difficulty in buffing.
- Ensure all wax residue is fully removed after application.
- Keep container sealed and store away from heat and sunlight.

7. Summary of Product Properties

- Product Type: Solid carnauba wax
- Usage per Vehicle: Approx. 30 g
- Durability: Approx. 1-2 months
- Core Functions: Gloss enhancement, shine improvement, protective film formation
- Application Method: Hand application and buffing
- Intended Use: Professional and OEM bulk supply
- Country of Origin: Japan

8. Remarks

- Designed for OEM bulk supply.
- Avoid storage in high-temperature environments.
- Test on a small, inconspicuous area before full application.
- Due to the nature of natural raw materials, slight variations in color or hardness may occur between lots.



Issued by:

NYS Inc.

4-3-12-508 Tsukiji, Chuo-ku, Tokyo 104-0045, Japan

TEL: +81-70-9002-4439

Email: info@nys-chemicals.jp

The information contained in this Technical Data Sheet is based on current technical knowledge at the time of publication.

Specifications and details are subject to change without prior notice.