



Technical Data Sheet (TDS)

Issued by:

NYS Inc.

4-3-12-508 Tsukiji, Chuo-ku, Tokyo 104-0045, Japan

TEL: +81-70-9002-4439

Email: info@nys-chemicals.jp

OEM WATER STAIN REMOVER STANDARD TYPE / HEAVY DUTY TYPE

Product Lineup

Standard Type

- OEM Water Stain Remover - Standard Type 150ml
- OEM Water Stain Remover - Standard Type 4L
- OEM Water Stain Remover - Standard Type 18L
- OEM Water Stain Remover - Standard Type 20L

Heavy Duty Type

- OEM Water Stain Remover - Heavy Duty Type 150ml
- OEM Water Stain Remover - Heavy Duty Type 4L
- OEM Water Stain Remover - Heavy Duty Type 18L
- OEM Water Stain Remover - Heavy Duty Type 20L

1. Product Concept

This product is a specialized cleaner developed to safely and effectively remove water stains from



automotive paint surfaces.

Its alkaline formulation penetrates and loosens water stains, while a specially blended fine powder captures and removes them efficiently in a short time.

It is safe for coated vehicles and provides a clear, streak-free finish.

Two product variations are available to suit different cleaning needs and contamination levels:

Standard Type

Compatible with all body colors. Despite being labeled “Standard,” it delivers powerful cleaning performance suitable for most applications.

Its gentle formula ensures safety for paint and coating layers, making it ideal for regular maintenance.

Heavy Duty Type

A reinforced version formulated for stubborn water stains and oxidized deposits that ordinary cleaners cannot remove.

It delivers strong penetration and cleaning performance for heavy buildup, achieving quick and reliable results.

2. Composition & Key Features

- Type: Water stain remover (Standard / Heavy Duty)
- pH: Alkaline
- Form: Liquid
- Recommended Usage Amount: Approx. 30 ml per vehicle
- Applicable Colors: All body colors
- Finish: Clear, glossy surface

Grade Configuration

- Standard Type
- Heavy Duty Type

Key Features

- Alkaline components lift stains while special fine powder particles securely remove them
- Extremely fine particles minimize damage to paint and coating surfaces



- Provides even, streak-free results in a short time
- Safe for use on coated vehicles
- Two strength levels available to match contamination severity

3. Performance & Characteristics

Cleaning Performance

Even the Standard Type provides excellent cleaning power, while the Heavy Duty Type effectively removes severe and hardened water stains.

Alkaline components lift stains, and the special powder formulation removes them completely.

Safety

Utilizes micro-particle abrasives that remove stains without cutting or damaging the paint surface.

Safe for new cars and coated vehicles.

Work Efficiency

Delivers a clean, uniform finish in a short time.

Ensures consistent results even over large surface areas.

4. Recommended Application Areas

- Entire vehicle body (doors, hood, roof, fenders, etc.)
- Coated vehicles requiring maintenance

5. Application Method

1. Rinse off dust, sand, and mud with high-pressure water.
2. On a wet surface, apply the product onto a sponge.
3. Spread evenly over the panel and gently rub to lift the stains.
4. Before the product dries, rinse thoroughly with plenty of water and wipe with a microfiber



towel.

(When using either type, do not leave the product on the surface for an extended time. Always wear protective gloves.)

6. Precautions During Application

- Avoid using under direct sunlight or on hot surfaces.
- Rinse thoroughly with water after application.
- Store tightly sealed, away from direct sunlight.
- For Heavy Duty Type, confirm contamination level before use.

7. Summary of Product Properties

- Product Type: Water stain remover (Standard / Heavy Duty)
- Form: Liquid
- Usage per Vehicle: Approx. 30 ml
- pH Level: Alkaline
- Cleaning Power:
 - Standard Type: High
 - Heavy Duty Type: Very high
- Material Safety: High
- Application Difficulty: Medium
- Country of Origin: Japan

8. Remarks

- This product is designed exclusively for water stain removal.
- For polishing or surface correction, use an appropriate polishing compound.
- This document is based on internal testing and practical application data and does not guarantee performance.



Issued by:

NYS Inc.

4-3-12-508 Tsukiji, Chuo-ku, Tokyo 104-0045, Japan

TEL: +81-70-9002-4439

Email: info@nys-chemicals.jp

The information contained in this Technical Data Sheet is based on current technical knowledge at the time of publication.

Specifications and details are subject to change without prior notice.