



Technical Data Sheet (TDS)

Issued by:

NYS Inc.

4-3-12-508 Tsukiji, Chuo-ku, Tokyo 104-0045, Japan

TEL: +81-70-9002-4439

Email: info@nys-chemicals.jp

OEM AUTO DEGREASER

Product Lineup

- OEM Auto Degreaser 50ml
- OEM Auto Degreaser 150ml
- OEM Auto Degreaser 4L
- OEM Auto Degreaser 18L
- OEM Auto Degreaser 20L

1. Product Concept

This product is a specialized degreaser developed exclusively for pre-coating surface preparation.

It chemically breaks down and removes wax, oil, and silicone residues remaining on paint, glass, and wheel surfaces after washing or polishing, creating a clean and uniform surface that ensures stable coating adhesion.

The simple wipe-on application using a microfiber cloth minimizes dependency on working conditions or operator skill level.



2. Composition & Key Features

- Type: Pre-coating surface cleaner (degreaser)
- Form: Liquid (solvent-based)
- Recommended Usage Amount: Approx. 36 ml per vehicle
- Applicable Materials: Paint, wheels, glass, chrome parts
- Finish: Uniform surface free of oil and residual films

Key Features

- Chemically dissolves and removes wax, oil, and silicone residues
- Simple wipe-on application without complex procedures
- Improves coating adhesion and long-term durability
- Designed to minimize dulling or whitening of painted surfaces
- Balanced formulation for professional use and safe handling

3. Performance & Characteristics

Degreasing Performance

Specialized solvent components penetrate and dissolve residual oils and surface films, forming a clean base suitable for coating application.

Safety

The formulation avoids overly aggressive solvents, reducing the risk of damage to painted or plastic surfaces.

Workability

Controlled volatility helps prevent streaking or residue, making it suitable for final degreasing after hand polishing or machine polishing.

4. Recommended Application Areas



- Automotive painted surfaces (hood, doors, roof, etc.)
- Aluminum wheels
- Chrome components
- Glass surfaces
- General pre-coating surface preparation

5. Application Method

1. Wash the surface and dry thoroughly.
2. Soak a microfiber cloth with the product.
3. Wipe the area evenly and gently — process complete.

(Do not scrub aggressively. Check for uniform wetting during application.)

6. Precautions During Application

- Do not use under direct sunlight or on hot surfaces.
- Reseal tightly and store in a cool, shaded area after use.

7. Summary of Product Properties

- Product Type: Pre-coating surface cleaner (degreaser)
- Form: Liquid (solvent-based)
- Usage per Vehicle: Approx. 36 ml
- pH Level: Neutral
- Material Safety: High
- Application Difficulty: Low
- Country of Origin: Japan



8. Remarks

- Designed exclusively for pre-coating surface preparation.
- For heavy tar or pitch contamination, use a dedicated cleaner.
- This document is based on internal testing and field data; performance is not guaranteed.

Issued by:

NYS Inc.

4-3-12-508 Tsukiji, Chuo-ku, Tokyo 104-0045, Japan

TEL: +81-70-9002-4439

Email: info@nys-chemicals.jp

The information contained in this Technical Data Sheet is based on current technical knowledge at the time of publication.

Specifications and details are subject to change without prior notice.