



# Technical Data Sheet (TDS)

Issued by:

NYS Inc.

4-3-12-508 Tsukiji, Chuo-ku, Tokyo 104-0045, Japan

TEL: +81-70-9002-4439

Email: [info@nys-chemicals.jp](mailto:info@nys-chemicals.jp)

## OEM GLUE REMOVER

### Product Lineup

- OEM Glue Remover 250ml
- OEM Glue Remover 500ml
- OEM Glue Remover 4L
- OEM Glue Remover 18L

### 1. Product Concept

This product is a professional-grade remover developed for safe and efficient removal of adhesive residues left after removing stickers, decals, or labels.

Its high-penetration solvent formulation softens hardened adhesive layers from within, allowing residues to be wiped away smoothly without scratching or damaging the surface.

The simple process — apply, allow time for penetration, and wipe off — makes it suitable for a wide range of applications, from professional use to general purposes.



## 2. Composition & Key Features

- Type: Adhesive remover (glue cleaner)
- Form: Liquid (solvent-based)
- Recommended Usage Amount: Approx. 25 ml per vehicle
- Applicable Materials: Painted surfaces, glass, stainless steel, aluminum
- Finish: Clean, residue-free surface

### Key Features

- Chemically dissolves and softens hardened adhesive residues
- No polishing or aggressive scrubbing required
- Moderate volatility provides sufficient penetration time
- Designed to minimize dulling or whitening of painted surfaces
- Stable removal performance suitable for professional use

## 3. Performance & Characteristics

### Removal Performance

Penetrates deeply into adhesive layers, softening and breaking down hardened or oxidized residues for easy removal.

### Safety

Balanced formulation designed to be safe for paint, glass, and metal surfaces, minimizing the risk of gloss loss or discoloration.

### Workability

Controlled evaporation rate allows adequate dwell time before wiping, reducing streaking and re-adhesion.

## 4. Recommended Application Areas

- Sticker or decal residue on vehicle body panels



- Adhesive residue after film installation or removal
- Glue marks on glass or metal surfaces
- Adhesive residue from household labels or price stickers

## 5. Application Method

1. Remove the sticker or film beforehand.
2. Apply product to a tissue or cloth and wipe over adhesive area.
3. Allow several minutes for penetration.
4. Wipe off softened glue with a clean cloth.
5. Wash the surface with car shampoo and dry with a clean microfiber towel.

(Repeat if necessary for stubborn residue.)

## 6. Precautions During Application

- For vinyl-type stickers, remove surface layer before applying product.
- Do not leave the product on surfaces for an extended time.
- Avoid use on plastic, acrylic, rubber, fabric, leather, or wood materials.
- Store tightly sealed, away from heat and direct sunlight.

## 7. Summary of Product Properties

- Product Type: Adhesive remover (glue cleaner)
- Form: Liquid (solvent-based)
- Usage per Vehicle: Approx. 25 ml
- Material Safety: High (paint, glass, metal safe)
- Application Difficulty: Low
- Country of Origin: Japan



## 8. Remarks

- Designed exclusively for adhesive residue removal.
- Always wash and wipe dry after use.
- This document is based on internal testing and field data; performance is not guaranteed.

Issued by:

NYS Inc.

4-3-12-508 Tsukiji, Chuo-ku, Tokyo 104-0045, Japan

TEL: +81-70-9002-4439

Email: [info@nys-chemicals.jp](mailto:info@nys-chemicals.jp)

The information contained in this Technical Data Sheet is based on current technical knowledge at the time of publication.

Specifications and details are subject to change without prior notice.