



Technical Data Sheet (TDS)

Issued by:

NYS Inc.

4-3-12-508 Tsukiji, Chuo-ku, Tokyo 104-0045, Japan

TEL: +81-70-9002-4439

Email: info@nys-chemicals.jp

OEM OIL-BASED HIGH GLOSS TIRE WAX

Product Lineup

- OEM Oil-Based High Gloss Tire Wax 150ml
- OEM Oil-Based High Gloss Tire Wax 4L
- OEM Oil-Based High Gloss Tire Wax 16L

1. Product Concept

This oil-based high gloss tire wax is specially developed for motor shows and showroom display vehicles.

It forms a strong protective coating that delivers a deep, premium gloss with excellent durability. Ideal for users seeking a professional-grade, luxurious tire finish.

2. Composition & Key Features



- Type: Oil-based tire wax (high gloss type)
- Form: Liquid
- Recommended Usage Amount: Approx. 40 ml per vehicle
- Applicable Materials: Rubber tires for automobiles and motorcycles
- Finish: Strong gloss with a thick, durable coating

Key Features

- Deep showroom-grade gloss
- Highly durable film with strong adhesion
- Excellent spreadability for high-gloss results with a small amount
- Professional-level finishing quality

3. Performance & Characteristics

The oil-based formula creates a rich, deep gloss suitable for high-end display vehicles.

Its strong protective film enhances durability and helps maintain a beautiful appearance for an extended period.

It spreads smoothly with minimal streaking, making it easy to apply for both professionals and general users.

4. Recommended Application Areas

- Automobile tires
- Motorcycle tires
- Rubber sidewalls
- Display vehicle tires requiring a high-gloss finish

5. Application Method

1. Rinse off dust, sand, and mud thoroughly with strong water pressure.
2. Wipe dry and ensure the tire surface is completely dry.



3. Apply the product to a sponge and spread thinly and evenly over the tire surface.
4. Check for excess product and wipe off any surplus if needed.

6. Precautions During Application

- Apply only when the tire is completely dry.
- Do not apply to hot tires immediately after driving.
- Avoid contact with brake components.
- Close the cap tightly after use and store properly.

7. Summary of Product Properties

- Oil-based high-gloss tire wax
- Recommended usage: Approx. 40 ml per vehicle
- Strong film formation with enhanced durability
- Designed for display vehicles and professional-grade finishing
- Country of Origin: Japan

8. Remarks

- Gloss durability may vary depending on tire condition.
- Shake well before use.
- Do not mix with other tire wax products.

Issued by:

NYS Inc.

4-3-12-508 Tsukiji, Chuo-ku, Tokyo 104-0045, Japan

TEL: +81-70-9002-4439

Email: info@nys-chemicals.jp



The information contained in this Technical Data Sheet is based on current technical knowledge at the time of publication.

Specifications and details are subject to change without prior notice.