



Technical Data Sheet (TDS)

Issued by:

NYS Inc.

4-3-12-508 Tsukiji, Chuo-ku, Tokyo 104-0045, Japan

TEL: +81-70-9002-4439

Email: info@nys-chemicals.jp

OEM WHEEL • TIRE CLEANER

Product Lineup

- OEM Wheel • Tire Cleaner 800ml
- OEM Wheel • Tire Cleaner 4L
- OEM Wheel • Tire Cleaner 18L
- OEM Wheel • Tire Cleaner 20L

1. Product Concept

This product is a powerful alkaline cleaner specifically designed for removing stubborn and bonded contamination such as baked-on brake dust and heavy grime.

Its active ingredients penetrate deeply into adhered dirt, lifting and removing it effectively. Despite its high cleaning strength, it maintains proven safety for wheel materials through extensive testing.

2. Composition & Key Features



- Type: Alkaline high-strength wheel and tire cleaner
- Form: Liquid
- Recommended Usage Amount: Approx. 16 ml per vehicle
- Applicable Materials: Aluminum, painted wheels, steel, chrome (patch test recommended)
- Finish: Strong cleaning and bonded dirt removal

Key Features

- Strong penetration for bonded brake dust
- High cleaning capability from alkaline active agents
- Proven material safety with proper use
- Efficient removal of heavy contamination with minimal effort

3. Performance & Characteristics

Alkaline cleaning agents penetrate deeply into accumulated brake dust and grime, lifting strongly adhered contamination for efficient removal.

It significantly reduces the heavy scrubbing typically required for long-term, bonded dirt.

Engineered for professional-level performance while maintaining balanced material safety.

4. Recommended Application Areas

- Wheel face (heavy contamination)
- Inner barrel bonded contamination
- Brake dust accumulation zones

5. Application Method

1. Rinse off loose dirt such as sand and mud with strong water pressure.
2. Without drying, spray the cleaner directly onto the wheel surface.
3. Lightly scrub with a sponge or brush.
4. Before the product dries, rinse thoroughly with plenty of water.



6. Precautions During Application

- For chrome wheels, always perform a patch test first.
- Avoid use on hot wheels or under direct sunlight.
- Do not allow the product to dry; rinse promptly to prevent staining.
- Multiple applications may be required for severe bonded contamination.

7. Summary of Product Properties

- Alkaline high-strength wheel and tire cleaner
- Recommended usage: Approx. 16 ml per vehicle
- Strong penetration and bonded dirt removal performance
- Spray application with light brushing
- Country of Origin: Japan

8. Remarks

- Patch test required for chrome or special finishes.
- Multiple applications may be needed for severe bonded grime.
- Shake well before use.

Issued by:

NYS Inc.

4-3-12-508 Tsukiji, Chuo-ku, Tokyo 104-0045, Japan

TEL: +81-70-9002-4439

Email: info@nys-chemicals.jp

The information contained in this Technical Data Sheet is based on current technical knowledge at



the time of publication.

Specifications and details are subject to change without prior notice.