



Technical Data Sheet (TDS)

Issued by:

NYS Inc.

4-3-12-508 Tsukiji, Chuo-ku, Tokyo 104-0045, Japan

TEL: +81-70-9002-4439

Email: info@nys-chemicals.jp

OEM CLAY BAR FOR WHEELS

Product Lineup

- OEM Clay Bar for Wheels 200g

1. Product Concept

This product is a wheel-specific clay bar designed to physically remove stubborn bonded contamination such as brake dust and metal particles that cannot be removed by chemicals alone. By combining a dedicated clay matrix with fine abrasive components, it effectively restores the wheel surface in a short time, even when contamination has been baked on by heat and friction during driving.

2. Composition & Key Features

- Type: Specialized clay bar for wheel contamination removal
- Form: Solid clay bar
- Recommended Usage Amount: Approx. 200 uses per bar (may vary depending on condition)



- Applicable Materials: Clear-coated and painted aluminum wheels
- Finish: Smoother wheel surface with bonded contaminants removed

Key Features

- Physically removes bonded contamination that detergents and solvents cannot dissolve
- Optimized balance of clay softness and abrasive strength
- Easy to handle, even for first-time users, with quick, visible results
- Ideal as a “last resort” when chemical cleaners are no longer effective

3. Performance & Characteristics

During driving, wheels can reach high temperatures, causing brake dust and metal particles to bake onto the surface.

The clay bar adheres to these bonded contaminants, and with the help of fine abrasives, lifts and removes them physically rather than chemically.

By carefully tuning clay softness, cutting power, and abrasive content, the product delivers strong decontamination performance while remaining manageable in real-world use.

When used with sufficient lubrication, it allows efficient removal of bonded deposits while minimizing unnecessary friction.

4. Recommended Application Areas

- Bonded brake dust on wheel faces
- Contamination around wheel spokes
- Stubborn deposits inside the inner barrel
- Remaining metal particles or bonded grime that chemicals cannot remove

5. Application Method

1. Rinse off dust, sand, and mud from the wheels with strong water pressure.
2. Wash the entire wheel thoroughly using a suitable wheel and tire cleaner, then rinse with



water.

3. Knead the clay into a flat shape and gently glide it over the wheel surface to remove bonded contaminants.

6. Precautions During Application

- Because contamination is removed by physical rubbing, fine scratches may occur.
- Do not apply excessive pressure; use light strokes and let the clay glide over the surface.
- For uncoated or special-finish wheels, always perform a patch test on an inconspicuous area first.
- Depending on the type and severity of the bonded contamination, complete removal may not always be possible.

7. Summary of Product Properties

- Specialized clay bar for wheel contamination removal
- Physical removal of bonded brake dust and metal particles
- Application difficulty: Medium
- Approx. 200 uses per bar (varies by contamination level)
- Country of Origin: Japan

8. Remarks

- If fine scratches become noticeable, follow up with a suitable wheel polish to refine the surface.
- Multiple applications may be required for contamination that has been neglected over long periods.
- After use, fold the clay to enclose contamination and expose a clean surface before the next use.



Issued by:

NYS Inc.

4-3-12-508 Tsukiji, Chuo-ku, Tokyo 104-0045, Japan

TEL: +81-70-9002-4439

Email: info@nys-chemicals.jp

The information contained in this Technical Data Sheet is based on current technical knowledge at the time of publication.

Specifications and details are subject to change without prior notice.